


Evo 3 IP

Evo3 Incremental Processor

The Evo 3 IP is an incremental processor in size 90 x 120 cm (36 x 48 inch). This unit has a separate pre-wash section for digital plates with a separate tank to contain the black layer and preserve the fresh solvent. This unit is delivered along with a stand alone punching device



WASHOUT SECTION




- Digital washout with separate pre-wash section to prevent contamination
- of the main washout solvent with black layer.
- 2 pre-wash brushes (oscillating and rotating)
- 8 washout brushes (oscillating and rotating)
- 1 top cleaning brush (oscillating and rotating)

- Constant solvent temperature thanks to water circulation serpentine
- The new "3D Brush Motion" system with servo drive motors enables a soft mechanical start
- which results in less vibrations and a much more quiet 3D machine. It also provides a constant and repeatable washout speed; in fact, the new system, adjustable from the display, automatically synchronizes the brushes rotation and oscillation speed to the plate transfer speed; so that bristles hit the plate, thin or thick, always at the same speed


OTHER FEATURES

- 30 x 30 touch screen display
- Programmable automatic solvent warmup
- Automatic standby after the last plate processed
- Remote access (optional)
- Active component visualisation during the process
- Manual function to run the components separately
- Memorisation of the plate process parameters (up to 24 channels)



- 1 wiping brush (oscillating and rotating)
- 2 back cleaning brushes (rotating)
- New volumetric pump and sensitive pressure sensor allow a higher precision solid content analyzer
- Automatic solvent replenishment system
- Fresh solvent consumption control over the machine life cycle and programmable over a time frame
- Fresh solvent flow regulation option on the touch screen





Dimensions LxWxH

 3730 x 1790 x 960 (panel 285) mm
146.8 x 70.5 x 37.8 (panel 11.2) inches

Power supply

 400V 3PH/N/PE 50/60Hz 6.5kW 10A
230V 3PH/PE 50/60Hz 6.5kW 18A

Plate thickness

 Up to 7 mm / 0.276 inch

Solvent

 min solvent volume for operation: 80 lts
max solvent volume for operation: 110 lts
max tank volume: 120 lts
solvent in & out pipes: 2 x 16 mm Ø

Packaging dimensions

 3830 x 2000 x 1380 mm | 1.350 Kg

Weight

1030 kg | 2271 pounds



Maximum plate size

92 x 120 cm | 36 x 48 inches



Compressed air supply

min. 7 bar



Exhaust

1 x 140 mm Ø - 600 m³/h



Remote monitoring

Optional



Vianord
engineering
www.vianord.com
info@vianord.com

© 2015 Vianord. All rights reserved. The Vianord Logo®, Easy to Plate™ and Evo™ are registered trademarks or trademarks of Vianord Engineering SAS or its affiliates. All technical information set out herein is provided free of charge and is based on technical data, which Vianord believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Vianord Engineering SAS reserves the right to change the specifications of its products at any time. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.