

## Evo4 Dryer

In addition to the innovative automatic units, Vianord also offers the standard dryer. This unit, for plates size up to 120 x 160 cm (47 x 63 inch), can be installed alone or combined with the Evo 4 LF on top.




### DRYER FEATURES

- 60 Celsius degree hot air (140 degree Fahrenheit)
- 6 drawers with individual timers
- 3 heating sections with separate temperature control and air circulation (2 drawers each)
- Uniform temperature for excellent drying result
- Safety thermostat in every section
- Exhaust system integrated
- Safety device for exhaust control
- Touch screen operator display
- Programmable unit warm up
- Automatic switch off after last plate







### Dimensions LxWxH

 1710 x 2030 x 1000 mm  
67.2 x 79.9 x 39.4 inches

### Power supply

 400V 3PH/N/PE 50/60Hz 4.8kW 8A  
230V 3PH/PE 50/60Hz 4.8kW 14A


### Plate thickness

 Up to 7 mm / 0.276 inch


### Solvent

 n/a

### Packaging dimensions

 2270 x 1940 x 1590 mm

### Weight

620 kg | 1364 pounds 


### Maximum plate size

120 x 160 cm | 47 x 63 inches 


### Compressed air supply

n/a 

### Exhaust

1 x 60 mm Ø - 80 m<sup>3</sup>/h 

### Packaging gross weights

1.050 Kg 



**Vianord**  
engineering  
[www.vianord.com](http://www.vianord.com)  
[info@vianord.com](mailto:info@vianord.com)

© 2015 Vianord. All rights reserved. The Vianord Logo®, Easy to Plate® and Evo® are registered trademarks or trademarks of Vianord Engineering SAS or its affiliates. All technical information set out herein is provided free of charge and is based on technical data, which Vianord believes to be reliable. It is intended for use by persons having skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use are outside of our control we make no warranties express or implied in relation thereto and therefore cannot accept any liability in connection with any use of this information. Vianord Engineering SAS reserves the right to change the specifications of its products at any time. Nothing herein is to be taken as a license to operate under, or a recommendation to infringe any patents.